Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mark: Luxus | | | | | | | |
|--|--------|----------------------------|--|--------------|--|--|--|
| Supplier's address: - | | | | | | | |
| Model identifier: 87011 | | | | | | | |
| | | | | | | | |
| Type of light source: | | | | | | | |
| Lighting technology used: | | LED | Non-directional or directional: | DLS | | | |
| Light source cap-type | | GU10 | | | | | |
| (or other electric interface) | | | | | | | |
| Mains or non-mains: | | NMLS | Connected light source (CLS): | Ne | | | |
| Colour-tuneable light source: | | Ne | Envelope: | - | | | |
| High luminance light source: | | Ne | | | | | |
| Anti-glare shield | d: | Ne | Dimmable: | No | | | |
| Product parameters | | | | | | | |
| Parameter | | Value | Parameter | Value | | | |
| General product parameters: | | | | | | | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 5 | Energy efficiency class | G | | | |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 380 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000 | | | |
| On-mode power (P _{on}), expressed in W | | 5,0 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | | | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 | | | |
| Outer dimensions without | Height | 53 | Spectral power | See image | | | |
| | Width | 50 | distribution in the | in last page | | | |
| | Depth | 50 | | | | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | range 250 nm to 800 nm, at full-load | | | | |
|--|------|--|-------|--|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | | |
| | | Chromaticity | 0,346 | | | |
| | | coordinates (x and y) | 0,359 | | | |
| Parameters for directional light sources: | | | | | | |
| Peak luminous intensity (cd) | 380 | Beam angle in degrees, or the range of beam angles that can be set | 120 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 6 | Survival factor | 0,90 | | | |
| the lumen maintenance factor | 0,93 | | | | | |

(a)'-': not applicable; (b)'-': not applicable;